

D-Link[®]
Building Networks for People

Audio & Video Surveillance for Home/Office

DCS-5300



- **CCD Sensor for Superior Quality Image**
- **Built-In Microphone for Audio Monitoring**
- **High Quality MPEG-4 Short Header Mode Compression**
- **Built-In Motion Detection & Email Notification**
- **A/V Output Enables Connection to TV & External Speakers**

SECURICAM[™] Network

10/100 Fast Ethernet Internet Camera

D-Link is pleased to introduce the newest product in Internet camera technology. Remotely watch and listen with the *D-Link SecuriCam DCS-5300 Internet Camera*. The DCS-5300 Internet Camera is a full-featured surveillance system that connects to an Ethernet or Fast Ethernet connection to provide high-quality video and audio over the Intranet or the Internet.

The DCS-5300 Internet Camera differs from a conventional PC Camera because the DCS-5300 is a stand-alone device with a built-in CPU and Web server that allows you to access your camera using Internet Explorer 5.X or above from anywhere in the world.

The D-Link DCS-5300 also has a pan and tilt function that can be controlled from the Web interface or from your remote control. Autopan mode enables the camera to move 270 degrees horizontally and the Patrol mode cycles through up to 24 preset positions. The speed of either pan or tilt can be adjusted to your preference.

The D-Link DCS-5300 comes with a CCD sensor that provides a sharp and clear image with life-like color representation. The sensor is a 1/4" CCD

sensor with resolution of 380 TV lines. The built-in microphone adds sound accompanies the video. All together, you can record streaming video that utilizes high quality MPEG-4 Short Header Mode Compression to your hard drive, enable motion detection, and set up automated email alert notification.

A powerful surveillance software is included to enhance the monitoring and management of your DCS-5300. The bundled surveillance software further enhances the security features of the DCS-5300, allowing you to archive streaming video straight to your hard drive, playback video, monitor as many as 16 cameras on a single screen, and set up motion detection to trigger automatic recording.

The D-Link DCS-5300 can be accessed and controlled remotely from any PC or notebook computer over the Internet from anywhere in the world. Simple installation procedures, along with the built-in Web-based interface provide a low-cost solution capable of meeting demanding security and home/office monitoring needs. Secure your site with D-Link SecuriCam.

**10/100
Mbps
SPEED**

**CCD
SENSOR**

**UPnP
Universal
Plug-&-Play**

**WEB
BASED
CONFIGURATION**

**FREE
24/7
TECH
SUPPORT
(USA ONLY)**

SECURICAM™ Network

10/100 Fast Ethernet

Internet Camera

SPECIFICATIONS

Power Input

- External Power Supply
- 12VDC 1.5A

Remote Management

Configuration and system log can be accessed via WEB Browser and FTP application remotely

Networking Protocol

TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS and DHCP

Network Application

- DDNS support with several popular DDNS servers
- UPnP support
- SMTP client
- FTP client
- FTP server
- HTTP server

Ethernet

10BaseT or 100BaseT Fast Ethernet

Video Algorithm Supported

H.263+ (MPEG4 Short Header Mode)

Features

- Three adjustable image sizes and quality intelligent motion detection windows with flexible bit rate
- MPEG4 short header mode compression for streaming video
- JPEG compression for still image

Audio

- 24Kbps
- Built-in omni-directional microphone

Video Resolution

- Up to 30fps at 160x120
- Up to 30fps at 320x240

General I/O

- 1 Opto-isolated sensor input (max. 12VDC 50mA)
- 1 relay output (max.24VDC 1A, 125VAC 0.5A)

Camera Specification

- 1/4 inch color CCD sensor
- AGC/AWB
- Electronic shutter: 1/60~1/15000 sec.
- Fixed focus glass lens, F2.0, 1 LUX

Pan and Tilt Direction Control

- Auto pan and auto patrol mode with preconfigured stops
- Pan: Range 270 degrees
- Tilt: Range 90 degrees

Ports

- 10/100 Mbps Fast Ethernet
- Audio/Video output
- External microphone input
- External I/O

Security

- Administrator and user group protected
- Password authentication

Viewing System Requirement Protocol

ActiveX

Operating System

Microsoft Windows® XP, 2000, Me or 98SE

Browser

Internet Explorer 5.x or above

LEDs

- 2 Status indicators.
- (1) Power
- (2) POST, connection, and heartbeat

Dimension

4.0" L x 4.1" W x 4.4 "H

Weight

12.2 oz.

Warranty

1 Year



*Audio & Video Surveillance
for Home/Office*



D-Link Systems, Inc. 17595 Mt. Hermann Fountain Valley CA 92708-4160 www.dlink.com
 ©Copyright D-Link Systems, Inc. 2003. All rights reserved. D-Link® is a registered trademark of D-Link Systems, Inc.
 Other trademarks or registered trademarks are the property of their respective manufacturers or owners.
 Price and specifications are subject to changes without notice. See inside package for warranty details.
 * 24/7 Tech Support is available only in USA.

D-Link®
Building Networks for People